

II. CLAIM AMENDMENTS

1. (Currently Amended) A method for binding a program module ~~{L1, L2, L3}~~ in a terminal ~~{MT}~~, in which one or several programs ~~{A, B}~~ are running, and in which method subroutines ~~{P1, P2, P3}~~ are stored in said program modules ~~{L1, L2, L3}~~, the program modules (L1, L2, L3) are provided with first tags ~~{T1, T2, T3}~~, wherein to start binding, the program makes a call ~~{7}~~ to a subroutine ~~{P1, P2, P3}~~, and the call ~~{7}~~ is supplemented with the first tags ~~{T1, T2, T3}~~ to select the program module ~~{L1, L2, L3}~~ for binding, in which the called subroutine ~~{P1, P2, P3}~~ is stored, ~~characterized in that~~ wherein the tags ~~{T1, T2, T3}~~ are supplemented with second tags ~~{LT1, LT2, LT3}~~, ~~that~~ the call ~~{7}~~ is also supplemented with said second call data ~~{PKx, PKy, PKz}~~, ~~and that~~ in connection with the binding, said first tags ~~{T1, T2, T3}~~ stored in the program modules are compared with the first tags ~~{T1, T2, T3}~~ transmitted in the call ~~{7}~~, and the second tags ~~{LT1, LT2, LT3}~~ are compared with the second call data ~~{PKx, PKy, PKz}~~ transmitted in the call ~~{7}~~, wherein and the program module to be bound is selected to be the program module which matches with the first tags ~~{T1, T2, T3}~~ and the second call data ~~{PKx, PKy, PKz}~~ transmitted in the call.

2. (Currently Amended) The method according to claim 1, ~~characterized in that~~ wherein the second tags ~~{LT1, LT2, LT3}~~ to be formed in the program modules contain a digital signature.

3. (Currently Amended) The method according to claim 2, ~~characterized in that~~ wherein the second call data are supplemented with a public key ~~{PKx, PKy, PKz}~~, on the basis of

BEST AVAILABLE COPY

which the digital signature of the second call data formed in the program module is verified.

4. (Currently Amended) The method according to claim 1, ~~characterized in that~~ wherein the second tags ~~{LT1, LT2, LT3}~~ to be formed in the program modules are stored in an encrypted form.

5. (Currently Amended) The method according to claim 4, ~~characterized in that~~ wherein the second call data are supplemented with a public key ~~{PKx, PKy, PKz}~~, on the basis of which the second tags ~~{LT1, LT2, LT3}~~ formed in the program modules are encrypted.

6. (Currently Amended) The method according to claim 1, in which program modules ~~{L1, L2, L3}~~ are stored in a server communicating with a digital network, ~~characterized in that~~ wherein the terminal ~~{MT}~~ used is a mobile terminal, and ~~that~~ the binding of the program modules ~~{L1, L2, L3}~~ is performed at least partly by messages complying with the WAP protocol.

7. (Currently Amended) A terminal ~~{MT}~~ comprising means ~~{H}~~ for binding a program module ~~{L1, L2, L3}~~, which program modules ~~{L1, L2, L3}~~ contain stored subroutines ~~{P1, P2, P3}~~ and first tags ~~{T1, T2, T3}~~, and which terminal ~~{MT}~~ also comprises means ~~{CTRL, MEM}~~ for running programs ~~{A, B}~~, means ~~{CTRL}~~ for starting binding by performing in the program a call ~~{7}~~ to a subroutine ~~{P1, P2, P3}~~, the call ~~{7}~~ being supplemented with first call data ~~{T1, T2, T3}~~ to select that program module ~~{L1, L2, L3}~~ for binding in which the called subroutine ~~{P1, P2, P3}~~ is stored, ~~characterized in that~~ wherein the program modules ~~{L1, L2, L3}~~ contain stored second tags ~~{LT1, LT2, LT3}~~; ~~that~~ the terminal

BEST AVAILABLE COPY

also comprises means ~~(CTRL, MEM)~~ for adding second call data ~~(PKx, PKy, PKz)~~ to the call ~~(7)~~, means ~~(H)~~ for comparing said first tags ~~(T1, T2, T3)~~ stored in the program modules with the first call data ~~(T1, T2, T3)~~ transmitted in the call ~~(7)~~, means ~~(H)~~ for comparing the second tags ~~(LT1, LT2, LT3)~~ with the second call data ~~(PKx, PKy, PKz)~~ transmitted in the call ~~(7)~~, and means ~~(H)~~ for selecting a program module to be bound on the basis of said comparison.

8. (Currently Amended) The terminal ~~(MT)~~ according to claim 7, ~~characterized in that~~ wherein the second tags ~~(LT1, LT2, LT3)~~ formed in the program modules contain a digital signature.

9. (Currently Amended) The terminal ~~(MT)~~ according to claim 8, ~~characterized in that~~ wherein the second call data are supplemented with a public key ~~(PKx, PKy, PKz)~~, on the basis of which the digital signature of the second tags formed in the program module are arranged to be verified.

10. (Currently Amended) The terminal ~~(MT)~~ according to claim 7, comprising means ~~(RF, DF, ANT)~~ for binding program modules ~~(L1, L2, L3)~~ stored in a server ~~(S)~~ communicating with the Internet network ~~(NW2)~~, ~~characterized in that~~ wherein the terminal ~~(MT)~~ is a mobile terminal, and that it comprises means ~~(CTRL)~~ for performing binding of the program modules ~~(L1, L2, L3)~~ at least partly by messages complying with the WAP protocol.

BEST AVAILABLE COPY